

In the Claims

1. (currently amended) A crimp-on edge clip for attachment to a print carrier sheet, comprising:

~~a clip portion configured for removable interface with a lock-up device carried by a print roll; and~~

~~a crimp fitting attached to the clip portion and configured to be crimped shut to secure a print carrier sheet to the edge clip.~~

a crimp fitting comprising an upper flange and a lower flange connected at an intersection and configured to be crimped shut to secure a print carrier sheet to the edge clip;

a clip portion integral with the crimp fitting and extending from the intersection of the upper flange with the lower flange; and

the edge clip forming a J-bar configured for removable interface with a lock-up device carried by a print roll.

2. (canceled)

3. (currently amended) The crimp-on edge clip of ~~claim 2~~ claim 1, wherein the edge clip is uniform in cross-section and elongated in a longitudinal direction.

4. (original) The crimp-on edge clip of claim 3, consisting essentially of a continuous extrusion.

5. (currently amended) A print carrier sheet comprising:
a backing having first and second opposing longitudinal edges extending in a longitudinal direction; and
~~an edge clip crimped to one or more of the edges.~~
a first edge clip crimped to the first edge comprising a crimp fitting having an upper flange and a lower flange connected at an intersection and an integral clip portion extending from the intersection, the first edge clip forming a first J-bar;
a second edge clip crimped to the second edge comprising a crimp fitting having an upper flange and a lower flange connected at an intersection and an integral clip portion extending from the intersection, the second edge clip forming a second J-bar;
and
the first and second J-bars configured for removable interface with opposing longitudinal rails of a lock-up device carried by a print roll.

6. (canceled)

7. (canceled)

8. (currently amended) The print carrier sheet of ~~claim 7~~ claim 5, wherein each ~~the~~ edge clip is uniform in cross-section and elongated in the ~~a~~ longitudinal direction.

9. (currently amended) The print carrier sheet of claim 8, wherein each ~~the~~ edge clip consists essentially of a continuous extrusion.

10. (currently amended) A print roll extending in a longitudinal direction and carrying a carrier sheet comprising:

~~a cylindrical print roll extending in a longitudinal direction along an axis of rotation;~~

a lock-up device carried by the print roll and comprising ~~a rail~~ first and second opposing rails extending in the longitudinal ~~longitudinally~~ direction; and

a print carrier sheet held to the print roll by the lock-up device and comprising:

~~a backing having a longitudinal edge, and~~

~~an edge clip crimped to edge and removably interfaced with the lock-up device.~~

a backing having first and second opposing edges extending in the longitudinal direction;

a first edge clip crimped to the first edge comprising a crimp fitting having an upper flange and a lower flange connected at an intersection and an integral clip portion extending from the intersection, the first edge clip forming a first J-bar that is removably interfaced with the first rail of the lock-up device; and

a second edge clip crimped to the second edge comprising a crimp fitting having an upper flange and a lower flange connected at an intersection and an integral clip portion extending from the intersection, the second edge clip forming a second J-bar that is removably interfaced with the second rail of the lock-up device.

11. (canceled)

12. (currently amended) The print roll of claim 10, wherein the each edge clip is uniform in cross-section and elongated in the ~~a~~ longitudinal direction.

13. (currently amended) The print roll of claim 10, wherein ~~the~~ each edge clip consists essentially of a continuous extrusion.

14. A printing machine, comprising:

a cylindrical print roll extending in a longitudinal direction along an axis of rotation;

a lock-up device carried by the print roll and comprising first and second rails extending in the longitudinal ~~longitudinally~~ direction;

a print carrier sheet held to the print roll by the lock-up device and comprising:

a backing having first and second ~~longitudinal~~ edges extending in the longitudinal direction;

a first edge clip crimped to the first edge ~~and comprising a crimp fitting having an upper flange and a lower flange connected at an intersection and an integral clip portion extending from the intersection, the first edge clip forming a first J-bar that is~~ removably interfaced with the a first rail of the lock-up device, and

a second edge clip crimped to the second edge ~~and comprising a crimp fitting having an upper flange and a lower flange connected at an intersection and an integral clip portion extending from the intersection, the second edge clip forming a second J-bar that is~~ removably interfaced with the a second rail of the lock-up device.

15. (currently amended) The printing machine sheet of claim 14, wherein each edge clip is uniform in cross-section and elongated in the a longitudinal direction.

16. (original) The printing machine of claim 15, wherein each edge clip consists essentially of a continuous extrusion.

17. (currently amended) A method for implementing crimp-on edge clips for a print carrier sheet, comprising the steps of:

providing a print carrier sheet backing having a first longitudinal edge;

providing a first edge clip that is uniform in cross-section and consists essentially of a continuous extrusion, the first edge clip comprising a crimp fitting having an upper flange and a lower flange connected at an intersection and an integral clip portion extending from the intersection, the first edge clip forming a first J-bar; and

crimping ~~an~~ the first edge clip to the first longitudinal edge.

18. (currently amended) The method of claim 17, further comprising the steps of:

providing a second longitudinal edge on the print carrier sheet backing;

providing a second edge clip that is uniform in cross-section and consists essentially of a continuous extrusion, the second edge clip comprising a crimp fitting having an upper flange and a lower flange connected at an intersection and an integral clip portion extending from the intersection, the second edge clip forming a second J-bar; and

crimping ~~an~~ the second edge clip to the second edge.

19. (original) The method of claim 18, further comprising the step of removably attaching the print carrier sheet to a print roll in a printing machine.

20. (original) The method of claim 19, further comprising the step of running the printing machine to print images using the print carrier sheet.

Respectfully submitted,



By: Michael J. Mehrman
Reg. No. 40,086

Mehrman Law Office, P.C.
5605 Glenridge Drive
Suite 795
Atlanta, GA 30342
404 497 7400 telephone
404 497 7405 facsimile
mike@mehrmanlaw.com